

# H.264 Series Triplex 4CH Real Time DVR

High Stability and Low Power Consumption,  
Suitable to Long Duration Application.



- ◆Advanced H.264 Technology
- ◆Advanced CMS Included
- ◆Recording Rate 240 CIF Frame
- ◆HDD Direct Playback
- ◆Remote Backup
- ◆Email Alert and FTP Upload
- ◆SATA II Compatible HDD & E-SATA for External HDD
- ◆Intelligent 3G/GPRS Surveillance on Operating Systems
- ◆PIP Display & Channel Screen Popup on Motion/Sensor
- ◆8 in 1 Remote Control
- ◆Multiple Network
- ◆750GB HDD Storage, 1500 Hours Full Recording Speed
- ◆Faster & Easier Search Function for Playback Retrieval
- ◆GUI (Graphical User Interface) for Easy Operation



3G/GPRS



SATA II



CMS



8 in 1 Remote Control



HDD Direct Playback



Network

# H.264 Series Triplex 4CH Real Time DVR

## Specification :

Specifications/Model		H-404	H-408	H-416
Video Input (NTSC/PAL)		4	8	16
Video Compression		H.264 (Internet Transmission : H.264)		
Video Output (VGA Optional)		BNC x 1 · VGA x 1		
Video Loop Out		BNC * 4	BNC * 8	BNC * 16
Audio Input		RCA x 4		
Audio Output		RCA x 1		
Sensor In/Alarm Out		4 Sensor In/1 Alarm Out	8 Sensor In/1 Alarm Out	16 Sensor In/1 Alarm Out
Display	Speed	100/120 fps	200/240 fps	400/480 fps
	Resolution (Pixels)	720 x 480 (NTSC) ; 720 x 576 (PAL)		
	Spilt Screen	1/4/SEQ	1/4/6/8/SEQ	1/4/8/13/16/SEQ
	Mode	Zoom x 2 · PIP · Auto SEQ		
Recording	Resolution (Pixels)	720 x 480 · 720 x 240 · 360 x 240 (NTSC)/720 x 576 · 720 x 288 · 360 x 288 (PAL)		
	Picture Quality	5 Levels (Highest · High · Normal · Low · Lowest)		
	Mode	Normal · Motion · Alarm · Schedule		
	Speed (Record)	60fps (720 x 480) · 120fps (720 x 240) · 240fps (352 x 240)/ 50fps (720 x 576) · 100fps (704 x 288) · 200fps (352 x 288)		
Playback	Display	1 · 4	1 · 4 · 8	1 · 4 · 9 · 16
	Speed (Playback)	30fps (720 x 480) · 60fps (720 x 240) · 120fps (352 x 240)/ 25fps (720 x 576) · 50fps (704 x 288) · 100fps (352 x 288)		
	Search	Time · Event · Calendar		
	Speed	Normal · REW & FF (2x · 4x · 8x · 16x · 32x · 64x) · Pause		
	Device	Support up to 2 Internal SATA HDDs or #1 SATA HDD & 1 e-SATA External DVD-Writer		Support up to 3 Internal SATA HDDs or 2 internal SATA HDDs & 1 e-SATA External DVD-Writer
Pre-Alarm Recording		16MB (approximate 8 seconds - 10 seconds)		
Backup Device		USB 2.0 · SATA CD Writer · SATA DVD Writer · Remote Network Backup		
	OSD	GUI (Graphic User Interface)		
	DVR Control	Remote Control · USB Mouse · USB Touch Panel		
	3G	Built-In (Mobile 5.0, 6.0 and Symbian support)		
Power		External Adaptor · AC100-240V/in · DC12V (5A)		

NOTE : Support D1, Half D1 and CIF.

Preliminary specifications are subject to change without notice.